



中国国家强制性产品认证证书

证书编号：2018010907081321

委托人名称、地址

深圳市玖洲宝科技有限公司

广东省深圳市宝安区沙井街道兴业西路12号金美威工业园第一栋厂房第四层

生产者（制造商）名称、地址

深圳市玖洲宝科技有限公司

广东省深圳市宝安区沙井街道兴业西路12号金美威工业园第一栋厂房第四层

生产企业名称、地址

深圳市玖洲宝科技有限公司

广东省深圳市宝安区沙井街道兴业西路12号金美威工业园第一栋厂房第四层

产品名称和系列、规格、型号

电源适配器

见附件（仅适用于海拔5000米及以下）

产品标准和技术要求

GB17625.1-2012; GB4943.1-2011; GB/T9254-2008

上述产品符合强制性产品认证实施规则 CNCA-C09-01:2014 的要求，
特发此证。

发证日期：2018年06月07日 有效期至：2023年06月07日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书的相关信息可通过国家认监委网站 www.cnca.gov.cn 查询



主任：



中国质量认证中心



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2018010907081321

NAME AND ADDRESS OF THE APPLICANT

Shenzhen Jiuzhou Power Technology Co., Ltd.
4/F First Block, Jinmeiwei First Industrial park, West of Xingye Road, Heyi Shajing Town, Baoan
District, Shenzhen, Guangdong, CHINA

NAME AND ADDRESS OF THE MANUFACTURER

Shenzhen Jiuzhou Power Technology Co., Ltd.
4/F First Block, Jinmeiwei First Industrial park, West of Xingye Road, Heyi Shajing Town, Baoan
District, Shenzhen, Guangdong, CHINA

NAME AND ADDRESS OF THE FACTORY

Shenzhen Jiuzhou Power Technology Co., Ltd.
4/F First Block, Jinmeiwei First Industrial park, West of Xingye Road, Heyi Shajing Town, Baoan
District, Shenzhen, Guangdong, CHINA

PRODUCT NAME, MODEL AND SPECIFICATION

See Appendix(Altitude up to 5000m)

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB17625.1-2012;GB4943.1-2011;GB/T9254-2008

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO.CNCA-C09-01:2014).

Valid from: Jun.07,2018

Valid until: Jun.07,2023

The validity of the certificate is subject to positive result of the regular follow up
inspection by issuing certification body until the expiry date.

The certificate information is available through CNCA's website: www.cnca.gov.cn



President:

Wang Kejiao



CHINA QUALITY CERTIFICATION CENTRE



中国国家强制性产品认证证书

附 录

第 1 页 共 1 页

证书编号: 2018010907081321

纸 号: 1968777

输入: 100-240Vac; 50/60Hz, 0.7A;

型号	输出电压 (V)	输出电流 (mA)	最大输出功率 (W)
JZB024-xxxxyyD (可移动式), JZB024-xxxxyyCX (直插式)	5.0-5.2	100-4000	20.8
	5.3-8.5	100-3700	22.1
	8.6-17.9	100-2600	24.0
	12.0	100-2500	30.0
	18.0-24.0	100-1330	24.0
注: xxx=050-240, 代表输出电压 5.0Vdc-24.0Vdc, 最小步进为 0.1V; yyy=010-400, 代表输出电流 0.1A-4.0A, 最小步进为 0.01A			

注: 此附录与证书同时使用时有效。



主 任:



中国质量认证中心